

RER70F II SERIES

Static load: 8000 Kg

Motors: 6 poles 50Hz



| RATIO | SHEAVE | SPEED | HP8 | HP9 | HP10 | HP11 | HP12 | HP14 |
|-------------|--------|-----------|------|------|------|------|------|------|
| | DIA/mm | m/sec | Kg | Kg | Kg | Kg | Kg | Kg |
| 65:1 | 520 | 0.39-0.42 | 1180 | 1260 | | | | |
| | 600 | 0.45-0.48 | 1020 | 1100 | | | | |
| | 650 | 0.49-0.52 | 940 | 1000 | | | | |
| | 700 | 0.52-0.56 | 860 | 940 | | | | |
| 55:1 | 520 | 0.46-0.49 | 1060 | 1200 | 1360 | 1460 | | |
| | 600 | 0.53-0.57 | 920 | 1060 | 1180 | 1280 | | |
| | 650 | 0.57-0.62 | 840 | 960 | 1080 | 1180 | | |
| | 700 | 0.62-0.67 | 760 | 860 | 980 | 1080 | | |
| 48:1 | 520 | 0.53-0.57 | 960 | 1100 | 1240 | 1380 | 1500 | |
| | 600 | 0.61-0.65 | 820 | 940 | 1060 | 1180 | 1300 | |
| | 650 | 0.66-0.71 | 740 | 840 | 960 | 1080 | 1200 | |
| | 700 | 0.71-0.76 | 660 | 740 | 860 | 980 | 1100 | |
| 38:1 | 520 | 0.67-0.72 | | 880 | 1020 | 1140 | 1260 | 1500 |
| | 600 | 0.77-0.83 | | 760 | 860 | 960 | 1060 | 1300 |
| | 650 | 0.83-0.89 | | 700 | 800 | 900 | 1000 | 1180 |
| | 700 | 0.90-0.96 | | 640 | 720 | 800 | 900 | 1060 |