

RER92F
 Static load: 8000 Kg
 Motors: 6 poles 50Hz



RATIO	SHEAVE	SPEED	HP14	HP16	HP18	HP20	HP22	HP24
	DIA/mm	m/sec	Kg	Kg	Kg	Kg	Kg	Kg
67:1	600	0.43-0.47	1800	2000	2300			
	700	0.51-0.55	1550	1700	1950			
	760	0.55-0.59	1400	1600	1800			
58:1	600	0.50-0.54	1700	1900	2200	2400		
	700	0.59-0.63	1450	1700	1850	2100		
	760	0.64-0.68	1350	1500	1700	1900		
46:1	600	0.63-0.68	1450	1600	1800	2000	2200	2450
	700	0.74-0.80	1200	1350	1550	1700	1900	2100
	760	0.80-0.86	1100	1200	1400	1550	1750	1900
66:2	600	0.88-0.95	1300	1400	1500	1700	1900	2100
	700	1.03-1.11	1000	1150	1300	1450	1600	1800
	760	1.12-1.20	900	1000	1150	1300	1450	1600
57:2	600	1.02-1.10	1000	1150	1300	1450	1600	1800
	700	1.19-1.28	850	950	1100	1250	1350	1500
	760	1.30-1.39	750	850	1000	1100	1250	1400